

IN THE CLAIMS

1. (Currently Amended) A disc drive comprising:
 - a disc rotationally coupled to a chassis;
 - a movable head suspension assembly having a head coupled thereto movable relative to a surface of the disc;
 - ~~an actuatable~~ transducer supported on the movable head suspension assembly and configured to induce a transducer signal proportional to movement of the head; and
 - a vibration detector configured to ~~receive the~~detect a transducer signal amplitude above a threshold
amplitude and output a level detected signal indicative of head vibration.
2. (Original) The disc drive of claim 1 wherein the level detected signal is indicative of head-disc contact.
3. (Currently Amended) The disc drive of claim 1 wherein the vibration detector includes a frequency filter.
4. (Previously Amended) The disc drive of claim 3 wherein the frequency filter is configured to detect at least one of a bending mode or torsion mode.
5. (Currently Amended) The disc drive of claim 1 wherein the ~~actuatable~~ transducer is a piezoelectric material.
6. (Currently Amended) The disc drive of claim 1 wherein the ~~actuatable~~ transducer is an electrostatic transducer.
7. (Previously Amended) The disc drive of claim 1 and further

comprising:

a process controller coupled to the detector and configured to receive the outputted level detected signal and output a process command to reexecute a write command in drive memory.

8. (Currently Amended) The disc drive of claim 1 and further comprising:

a controller coupled to the ~~actuatable~~ transducer on the movable head suspension assembly and configured to transmit a signal to the ~~actuatable~~ transducer to move the head.

9. (Currently Amended) The disc drive of claim 1 wherein the disc drive includes a plurality of discs rotationally coupled to the chassis and a plurality of movable head suspension assemblies having heads coupled thereto to read or write to surfaces of the plurality of discs and including an ~~actuatable~~ transducer coupled to each of the plurality of movable head suspension assemblies.

10. (Currently Amended) The disc drive of claim ~~1~~19 wherein the ~~actuatable~~ transducer is configured to operate between a detection mode and an actuation mode, in the detection mode, the ~~actuatable~~ transducer detecting the head vibration associated with the head suspension assembly and in the actuation mode the ~~actuatable~~ transducer receiving a signal to energize the ~~actuatable~~ transducer to move the head of the head suspension assembly.

11. (Currently Amended) The disc drive of claim 10 including:

a microactuator controller coupled to the ~~actuatable~~ transducer and configured to operate the ~~actuatable~~ transducer in the actuation mode.

12. (Previously Amended) A method for operating a disc drive comprising steps of:

- (a) providing a transducer supported on a movable head suspension assembly having a head coupled thereto configured to generate a transducer signal indicative of head vibration; and
- (b) detecting a signal amplitude of the transducer signal above a threshold amplitude and outputting a level detected signal indicative of the head vibration.

13. (Previously Amended) The method of claim 12 wherein the transducer is a piezoelectric transducer.

14. (Previously Amended) The method of claim 12 and further comprising the step of:

- (c) transmitting a signal to the transducer on the movable suspension assembly to move the head.

15. (Previously Amended) The method of claim 12 and further comprising the step of:

- (c) transmitting a command to rewrite a write command in drive memory in response to the level detected signal indicative of the head vibration.

16. (Previously Amended) The method of claim 12 and comprising the step of

- (c) filtering the transducer signal to detect vibration frequencies of the head.

17. (Previously Amended) The method of claim 12 wherein the disc drive includes a plurality of head suspension assemblies and

further comprising:

- (c) individually detecting the head vibration for each of the plurality of head suspension assemblies.

18. (Previously Amended) The method of claim 12 including a microactuator controller coupled to the transducer and configured to transmit a signal to the transducer to move the head and comprising the step of:

- (c) selectively operating the disc drive in a detection mode and an actuation mode, in the detection mode the transducer detecting the head vibration and in the actuation mode, the transducer moving the head.

19. (Currently Amended) A drive assembly comprising:

- a movable head suspension assembly; and
- a detector coupled to a transducer on the movable head suspension assembly that provides a signal indicative of a vibration associated with the head suspension assembly and the detector outputs a level detected signal that is responsive to the vibration being greater than a threshold value.

20. (Previously Amended) The method of claim 12 and comprising the step of:

- (c) filtering the transducer signal to detect one of bending or torsion mode vibration frequencies.

21. (Previously Added) The assembly of claim 19 in which the vibration is caused by head vibration.

22. (Previously Added) The assembly of claim 19 wherein the detector includes a filter configured to pass a signal responsive

to vibration frequencies associated with the head suspension assembly.

23. (Currently Amended) An assembly comprising:
a movable suspension assembly;
an actuator coupled to the movable suspension assembly;
and
a detector coupled to the actuator and configured to
receive a signal from the actuator proportional to
vibration of the movable suspension assembly.

24. (Previously Added) The assembly of claim 23 wherein the actuator is one of a piezoelectric or electrostatic actuator.

25. (Previously Added) The assembly of claim 23 and further comprising:
a controller coupled to the actuator and configured to
transmit a signal to the actuator to move the
movable suspension assembly.

26. (Previously Added) The assembly of claim 23 including a controller configured to operate the actuator between an actuation mode to position a head of the movable suspension assembly and a detection mode to detect vibration of the head of the movable suspension assembly.